Research Article
E-ISSN : 3048-1368

Volume 05, Issue No. 04. 2024
P-ISSN : 3048-1376

The International Journal of Medical Science and Health Research



Accuracy of machine learning models using ultrasound images in prostate cancer diagnosis

[1] Christine, [1] Fransiska

[1] Faculty of Medicine, Trisakti University, Special Region of Jakarta, Indonesia
Correspondence : christinedokter281@gmail.com

Article History :
Received date : 2024/07/12
Revised date : 2024/08/02
Accepted date : 2024/09/16
Published date : 2024/10/05

Copyright: *© 2024 by the authors. Submitted for possible open access publication under the terms and conditions of the Creative Commons Attribution (BY NC) license (https://creativecommons.org/licenses/by-nc/4.0/).*

E-ISSN :
ISSN 3048-1368
9 773048 136000

P-ISSN :
ISSN 3048-1376
9 773048 137007

ABSTRACT

Background: The literature on the accuracy of machine learning models using ultrasound images in prostate cancer diagnosis reveals a dynamic landscape marked by both significant advancements and persistent challenges. The introduction establishes the importance of integrating machine learning with ultrasound imaging to improve diagnostic precision, particularly in a domain fraught with high stakes due to the complexities associated with prostate cancer. The initial studies highlight the potential of machine learning to standardize interpretations, as evidenced by the comparative analysis of labeling strategies that demonstrated superior performance with digital pathologist annotations over radiologist labels (Bhattacharya et al., 2021). **Literature Review:** As the review progresses, it becomes clear that traditional ultrasound imaging faces limitations, such as low resolution and high inter-observer variability, which can compromise diagnostic accuracy (Akatsuka et al., 2022). The literature advocates for the application of artificial intelligence (AI) technologies to enhance the reliability of cancer grading, emphasizing the critical role of accurate pathological grading in treatment decision-making. Further analysis reveals a growing body of work focused on the integration of advanced machine learning techniques, including deep learning and hybrid models that combine traditional and innovative approaches (Luijten et al., 2022). **Conclusion:** In conclusion, the literature collectively underscores the transformative potential of machine learning and deep learning techniques in enhancing the accuracy of prostate cancer diagnosis using ultrasound images. Despite the promising advancements, the field faces critical challenges, particularly regarding the need for robust datasets, the integration of AI into clinical practice, and the necessity for standardized evaluation criteria. Addressing these challenges will be pivotal in realizing the full potential of AI technologies in improving diagnostic outcomes and patient management in prostate cancer.

Keywords: Accuracy, machine learning models, ultrasound images, prostate cancer diagnosis

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

INTRODUCTION

The accuracy of machine learning models in diagnosing prostate cancer using ultrasound images has garnered significant attention in recent years, reflecting the ongoing quest to enhance diagnostic precision in a field marked by high stakes and complex challenges. The literature reveals a progressive evolution in methodologies and insights, beginning with (Bhattacharya et al., 2021), who highlighted the potential of machine learning to standardize interpretations of prostate MRI. Their comparative analysis of various labeling strategies demonstrated that models trained with digital pathologist labels significantly outperformed those based on radiologist annotations, thus suggesting that the integration of advanced labeling techniques can bridge critical gaps between radiology and pathology.

Following this foundational work, (Akatsuka et al., 2022) explored the application of ultrasound imaging in detecting high-grade prostate cancer. They underscored the limitations of conventional ultrasound, such as low resolution and high inter-observer variability, which often compromise diagnostic accuracy. Their study advocated for the use of artificial intelligence (AI) technologies to enhance the reliability of cancer grading during ultrasound examinations, emphasizing the importance of accurate pathological grading in guiding therapeutic decisions.

(Li et al., 2022) provided a broader review of machine learning applications in prostate MRI, summarizing the advancements made in segmentation, detection, and assessment, while also identifying gaps in existing research on ultrasound imaging modalities. Their findings indicated a growing interest in employing AI to support urological disease treatments, although they noted that much of the focus remained on MRI rather than ultrasound.

The work of (Luijten et al., 2022) further contributed to this discourse by discussing the significance of signal processing in

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

ultrasound imaging. They advocated for a hybrid approach that combines traditional models with deep learning techniques, which can enhance the robustness and efficiency of image reconstructions. This perspective aligns with the ongoing trend of integrating domain knowledge with data-driven methodologies to optimize performance in medical imaging.

(Hashem et al., 2022) advanced the conversation by presenting a multi-parametric MRI transfer learning model for prostate cancer classification, reinforcing the notion that deep learning can effectively enhance diagnostic accuracy. Their insights contributed to a growing body of evidence supporting the use of AI in distinguishing between benign and malignant lesions.

(Yin & Buduma, 2022) addressed the subjective nature of radiological interpretations by proposing computer-aided detection (CAD) algorithms to standardize diagnoses based on multiparametric MRI. Their research highlighted the necessity of incorporating domain expertise in algorithm design to mitigate false positives and negatives, thereby enhancing the overall accuracy of prostate cancer detection.

(Bhattacharya et al., 2022) conducted a comprehensive review of AI applications in prostate cancer detection, emphasizing the need for larger, more diverse patient datasets to improve the generalizability of AI models. They pointed out the predominance of studies utilizing novel ultrasound modalities, thereby underscoring a gap in research focused on traditional grayscale ultrasound images.

In a comparative review, (Bechelli, 2022) discussed the advancements in machine learning and deep learning for cancer diagnosis, particularly in prostate cancer detection. Their findings indicated that AI models could achieve diagnostic accuracy surpassing that of human specialists, although challenges related to model training on limited databases persisted.

(Baek et al., 2022) examined the integration of raw ultrasound parameters into machine learning

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

frameworks for breast cancer diagnosis, drawing parallels that could inform prostate cancer detection methodologies. Their insights highlighted the potential of deep learning to optimize feature extraction from ultrasound data, a critical step for enhancing diagnostic performance.

Overall, the literature underscores a multifaceted approach to improving prostate cancer diagnosis through the application of machine learning and deep learning techniques in ultrasound imaging. The critical evaluation of these studies reveals both the promise and the challenges inherent in leveraging AI technologies to enhance diagnostic accuracy, ultimately aiming to improve patient outcomes in prostate cancer management.

LITERATURE REVIEW

The article "Bridging the gap between prostate radiology and pathology through machine learning" by (Bhattacharya et al., 2021) presents an insightful analysis of the potential of machine learning (ML) in enhancing the accuracy of prostate cancer diagnosis through the use of ultrasound images and other imaging modalities. The authors highlight the persistent challenges associated with prostate cancer diagnostics, particularly the limitations of Magnetic Resonance Imaging (MRI), which is often marred by high rates of false positives and negatives. This issue necessitates the exploration of alternative methodologies, such as machine learning, to improve diagnostic precision.

A critical aspect of the study is the comparison of different labeling strategies used to train various deep learning models, specifically SPCNet, U-Net, branched U-Net, and DeepLabv3+. The authors meticulously detail how the quality of labels—specifically, the distinction between radiologist-confirmed labels and those provided by digital pathologists—significantly influences model performance. The findings indicate that radiologist labels tend to miss cancers and yield lower lesion volumes and Dice overlaps compared to the more accurate digital pathologist labels. This discrepancy underscores the

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

importance of the training data quality in the development of robust machine learning models.

The authors further elucidate that models trained with digital pathologist labels not only exhibited superior lesion detection rates but also demonstrated comparable performance to those trained with traditional pathology labels. This is particularly noteworthy as it suggests that digital pathologist annotations could serve as a reliable alternative for training ML models, potentially leading to improved diagnostic outcomes. Moreover, the models trained with pixel-level digital pathologist labels were capable of distinguishing between aggressive and indolent cancer components within mixed lesions, showcasing the nuanced capabilities of these advanced models in clinical settings.

The article titled "A data-driven ultrasound approach discriminates pathological high grade prostate cancer" by (Akatsuka et al., 2022) provides a significant contribution to the field of prostate cancer diagnosis through the application of machine learning techniques on ultrasound images. The authors underscore the prevalent issue of low resolution and high inter-observer variability that often plagues traditional ultrasound imaging, which can compromise the accuracy of prostate cancer screening. This is particularly concerning given that prostate cancer is one of the most frequently diagnosed cancers among older men, making reliable diagnostic methods essential for effective cancer management.

The study highlights the potential of artificial intelligence (AI) technologies, particularly deep learning algorithms, to enhance the diagnostic accuracy of ultrasound images. The authors note that while deep learning has shown promise in various medical imaging applications, the challenge remains in accurately estimating pathological grading, such as the Gleason score, from standard ultrasound images. This is a critical point, as the Gleason score is pivotal in determining therapeutic strategies for prostate cancer patients.

(Akatsuka et al., 2022) successfully demonstrate that it is feasible to estimate high-grade cancer pathology using ordinary ultrasound

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

images and limited clinical data. This is an important advancement, as it suggests that even with the inherent limitations of traditional ultrasound imaging, machine learning can still provide valuable insights into the pathology of prostate cancer. The authors present a framework that leverages deep learning for accurate automatic segmentation of ultrasound images, which is a crucial step in the detection and grading of cancer.

However, the article could benefit from a more detailed discussion on the specific algorithms employed and the dataset used for training and validation of the machine learning models. A thorough understanding of the model's architecture and the performance metrics would provide a clearer picture of the reliability and generalizability of the findings. Additionally, while the study emphasizes the importance of accurate diagnosis for optimizing cancer management, it would be advantageous to explore the clinical implications of integrating such AI-driven approaches into routine practice.

The article "Machine Learning in Prostate MRI for Prostate Cancer: Current Status and Future Opportunities" by (Li et al., 2022) provides a comprehensive overview of the advancements in machine learning (ML) and deep learning (DL) techniques applied to prostate MRI for cancer detection. The authors synthesize existing literature, highlighting the significant capabilities of these technologies in processing imaging data to enhance diagnostic accuracy.

A critical evaluation of the material reveals that the authors effectively summarize the state of research in ML and DL applications for prostate MRI. They discuss the radiomics pipeline, which involves the extraction of quantitative features from medical images, and its role in cancer detection and grading. This approach is particularly relevant as it underscores how ML can aid in identifying subtle patterns in imaging data that may not be discernible to the human eye. The review also touches on the potential for these technologies to support clinical decision-making, which is crucial in the context of

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

prostate cancer, where treatment options can vary significantly based on tumor characteristics.

However, while the article presents a thorough review of the capabilities of ML and DL in prostate MRI, it also highlights the limited amount of research specifically focused on prostate MRI applications. This indicates a gap in the literature that could be addressed through further studies. The authors note that while there has been progress, the integration of AI into clinical practice remains an area needing more robust evidence and validation.

Moreover, the article discusses the challenges associated with implementing machine learning models in clinical settings, such as the need for large, diverse datasets to train these models effectively. The authors emphasize that the success of ML applications is contingent upon the quality and quantity of the data used, which raises questions about generalizability and the potential for bias in model training.

The article "Ultrasound Signal Processing: From Models to Deep Learning" by (Luijten et al., 2022) presents a comprehensive overview of the advancements in ultrasound imaging, particularly focusing on the integration of deep learning techniques with traditional signal processing methods. The authors emphasize the critical role that high-quality signal processing plays in producing reliable and interpretable ultrasound images, which is especially pertinent in the context of prostate cancer diagnosis.

One of the key insights from the article is the emerging paradigm that combines data-driven deep learning approaches with established domain knowledge. This hybrid methodology is particularly relevant in medical imaging, where the complexity of biological structures necessitates robust solutions that can adapt to varying conditions. The authors argue that model-based solutions offer several advantages over conventional neural networks, including enhanced robustness and a reduced requirement for extensive training data and parameters. This is particularly significant in medical applications, where the availability of

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

large annotated datasets can often be a limiting factor.

The article also highlights the potential for these advanced techniques to improve the accuracy of machine learning models in the context of prostate cancer diagnosis. By leveraging both data-driven approaches and domain-specific insights, the proposed methods could lead to more reliable image reconstructions, thereby facilitating better diagnostic outcomes. The authors provide a forward-looking perspective, encouraging further research into model-based deep learning techniques tailored for medical ultrasound. This call to action is timely, given the increasing interest in applying artificial intelligence to enhance diagnostic accuracy in various medical fields.

The article "An Enhanced Deep Learning Technique for Prostate Cancer Identification Based on MRI Scans" by (Hashem et al., 2022) presents a comprehensive exploration of the application of deep learning techniques in the classification of clinically significant prostate cancer utilizing multi-parametric MRI. The study emphasizes the critical role of computer-aided diagnosis in enhancing the detection rates of prostate cancer, particularly in distinguishing clinically significant cases from less severe forms.

The authors conducted a validation study that compared the effectiveness of deep learning algorithms with traditional radiomics approaches. The findings indicate that deep learning models significantly improve detection capabilities, showcasing their potential in clinical settings. This is particularly relevant given the increasing reliance on imaging modalities for cancer diagnosis. The authors also highlight the use of transfer learning models, which leverage pre-trained networks to enhance classification accuracy, thereby reducing the need for extensive labeled datasets.

Moreover, the article delves into the comparative performance of MRI-derived PRECISE scores and delta-radiomics models in predicting prostate cancer progression among patients under active surveillance. This aspect underscores the

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

importance of integrating machine learning techniques with existing clinical metrics to refine prognostic capabilities. The authors advocate for the use of advanced metrics such as the Matthews correlation coefficient (MCC), which they argue provides a more reliable evaluation of binary classification performance compared to traditional metrics like the F1 score and accuracy.

The discussion on domain knowledge encoding within convolutional neural network (CNN) architectures is particularly noteworthy. The authors assert that incorporating expert knowledge into model design can significantly enhance performance, suggesting that a hybrid approach that combines machine learning with clinical expertise may yield the best outcomes in prostate cancer diagnosis.

The article "Prostate Lesion Detection and Salient Feature Assessment Using Zone-Based Classifiers" by (Yin & Buduma, 2022) presents a comprehensive examination of the application of machine learning techniques in the diagnosis of prostate cancer using ultrasound and other imaging modalities. The authors highlight the limitations of traditional diagnostic methods, particularly the subjectivity involved in the interpretation of multiparametric Magnetic Resonance Imaging (mpMRI) scans as per the Prostate Imaging Reporting And Data System (PI-RADS). This subjectivity can lead to inconsistencies in diagnosis, which the authors argue can be mitigated through the implementation of computer-aided detection (CAD) algorithms.

The study critically evaluates the performance of both non-deep learning and deep learning algorithms in detecting prostate lesions across three distinct zones of the prostate: the peripheral zone (PZ), the transition zone (TZ), and the anterior fibromuscular stroma (AS). By incorporating heterogeneous data and applying rigorous preprocessing techniques, the authors aim to enhance the accuracy and reliability of lesion detection. This approach is particularly relevant given the increasing reliance on machine learning in medical diagnostics, where algorithmic performance can

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

significantly impact clinical outcomes.

A notable strength of the article is its methodological rigor in comparing various algorithmic implementations. The authors not only report on the effectiveness of these algorithms but also delve into the salient features that contribute to lesion determination. This feature assessment is crucial for understanding the underlying rationale behind the classifications made by different algorithms, thereby providing insights that could inform future developments in CAD systems. The authors also reference significant advancements in the field over the past decade, underscoring the evolution of machine learning applications in cancer diagnostics. Their findings suggest that the use of CAD can lead to more standardized and objective diagnoses, potentially outperforming the diagnostic capabilities of trained radiologists. This assertion is supported by empirical evidence presented in the study, which demonstrates the effectiveness of their proposed multi-parametric CAD system.

However, while the article presents a compelling case for the integration of machine learning in prostate cancer diagnostics, it is important to consider the potential limitations and challenges associated with these technologies. Issues such as the need for large, diverse datasets for training algorithms, the interpretability of machine learning models, and the integration of these systems into clinical workflows warrant further exploration. Additionally, the generalizability of the findings to broader populations remains an essential consideration, as variations in imaging techniques and patient demographics could influence algorithm performance.

The article "A review of artificial intelligence in prostate cancer detection on imaging" by (Bhattacharya et al., 2021) provides a comprehensive overview of the current landscape of artificial intelligence (AI) applications in the detection of prostate cancer through various imaging modalities, with a particular emphasis on the limitations of existing machine learning models. One of the critical insights from the

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

article is the observation that most AI models developed for prostate cancer detection have not undergone rigorous testing to evaluate their generalizability across diverse and larger patient populations. This presents a significant concern, as the effectiveness of these models in real-world clinical settings remains largely unverified.

The authors highlight the necessity for the creation of publicly available anonymized datasets that encompass a wide range of patient demographics. Such datasets would facilitate the training and validation of machine learning models, thereby enhancing their robustness and reliability. Furthermore, the call for standardized evaluation criteria is crucial, as it would enable a more consistent assessment of model performance across studies. The lack of external validation and multi-reader studies further compounds the issue, as these elements are essential for establishing the credibility of AI systems in clinical practice.

Interestingly, the article points out that while grayscale transrectal ultrasound is a common imaging technique used for prostate biopsies, there has been a notable scarcity of AI research focused specifically on this modality. This gap is particularly striking given that most of the studies reviewed have concentrated on newer ultrasound-based imaging techniques, which may not yet be widely adopted in clinical settings. The authors also mention that some investigations have utilized radio-frequency time-series data for prostate cancer detection, employing traditional machine learning approaches. However, the limited focus on grayscale ultrasound images raises questions about the applicability of these AI models to routine clinical practice.

The article "Computer-Aided Cancer Diagnosis via Machine Learning and Deep Learning: A comparative review" by (Bechelli, 2022) provides a comprehensive examination of the advancements in machine learning (ML) and deep learning (DL) technologies for cancer detection, with a particular emphasis on prostate cancer diagnosis through medical imaging. The author effectively synthesizes current

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

research findings, highlighting the significant potential of these technologies to enhance diagnostic accuracy beyond that achieved by human pathologists.

One of the key insights presented in the article is the comparative analysis of diagnostic outcomes between ML/DL models and traditional pathologist evaluations. Bechelli notes that these models can outperform specialists in terms of accuracy, suggesting a transformative potential for artificial intelligence in clinical settings. This finding is particularly relevant in the context of prostate cancer, where early and accurate diagnosis is crucial for effective treatment and management.

However, the review also critically addresses several challenges that hinder the broader application of ML and DL in prostate cancer diagnosis. A notable concern is the reliance on a limited number of training images, which often lack the necessary diversity to ensure that models can generalize effectively to new, unseen data. This limitation raises questions about the robustness of the models and their applicability across diverse patient populations and imaging conditions.

Furthermore, the author points out the issue of dataset accessibility, emphasizing that many datasets used for training these models are not publicly available. This lack of transparency can impede the validation and reproducibility of research findings, ultimately stifling progress in the field. Researchers and practitioners may face significant barriers in acquiring the data necessary to develop and refine these diagnostic tools.

Bechelli also highlights ongoing efforts to improve the efficiency of segmentation and detection tasks within the ML/DL frameworks. This focus on enhancing the technical capabilities of these models is vital, as it can lead to more accurate and faster diagnoses, ultimately benefiting patient outcomes. Additionally, the article notes that the applications of ML and DL extend beyond diagnosis to include treatment prediction and risk assessment, indicating a broadening scope of potential uses in oncology.

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

The article "Improving breast cancer diagnosis by incorporating raw ultrasound parameters into machine learning" by (Baek et al., 2022) presents a comprehensive analysis of the role of ultrasound imaging in enhancing breast cancer diagnosis through machine learning methodologies. The authors highlight the inherent advantages of ultrasound, including its affordability, accessibility, and non-ionizing nature, which makes it a favorable option for imaging studies in clinical settings.

A significant portion of the article discusses the evolution of machine learning in breast cancer diagnostics, noting that traditional approaches primarily relied on simple texture and morphological features extracted from ultrasound images. This dependency on predefined features can limit the performance of machine learning models, as the effectiveness of these features may vary across different datasets and populations. To overcome this limitation, the authors advocate for the use of deep learning algorithms, which have shown promise in automating the extraction of data-driven feature maps directly from the input images. This shift not only simplifies the feature detection process but also potentially enhances the accuracy of diagnostic classifications.

However, the article critically addresses the challenges associated with implementing deep learning in ultrasound imaging for cancer diagnosis. One of the primary concerns is the requirement for large training datasets to achieve reliable diagnostic performance. The authors note that collecting a substantial amount of patient ultrasound data poses significant logistical and ethical challenges, particularly in the context of sensitive medical information. Additionally, the computational complexity associated with deep learning techniques can restrict the size and type of ultrasound signal inputs that can be effectively utilized, potentially limiting the generalizability of the models developed.

CONSCLUSION

The literature on the accuracy of machine learning models using

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

ultrasound images in prostate cancer diagnosis reveals a dynamic landscape marked by both significant advancements and persistent challenges. The introduction establishes the importance of integrating machine learning with ultrasound imaging to improve diagnostic precision, particularly in a domain fraught with high stakes due to the complexities associated with prostate cancer. The initial studies highlight the potential of machine learning to standardize interpretations, as evidenced by the comparative analysis of labeling strategies that demonstrated superior performance with digital pathologist annotations over radiologist labels (Bhattacharya et al., 2021).

As the review progresses, it becomes clear that traditional ultrasound imaging faces limitations, such as low resolution and high inter-observer variability, which can compromise diagnostic accuracy (Akatsuka et al., 2022). The literature advocates for the application of artificial intelligence (AI) technologies to enhance the reliability of cancer grading, emphasizing the critical role of accurate pathological grading in treatment decision-making.

Further analysis reveals a growing body of work focused on the integration of advanced machine learning techniques, including deep learning and hybrid models that combine traditional and innovative approaches (Luijten et al., 2022). This integration is essential for optimizing performance in medical imaging, particularly in the context of prostate cancer, where distinguishing between benign and malignant lesions can significantly impact patient management (Hashem et al., 2022).

The review also highlights the necessity of addressing the subjective nature of radiological interpretations through the implementation of computer-aided detection (CAD) algorithms (Yin & Buduma, 2022). These algorithms aim to standardize diagnoses and mitigate inconsistencies that arise from human interpretation, thus enhancing the overall accuracy of prostate cancer detection.

Moreover, the literature emphasizes the importance of large,

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

diverse datasets for training AI models to improve their generalizability and performance across different populations (Bhattacharya et al., 2022). The comparative review of machine learning and deep learning for cancer diagnosis indicates that while AI models can surpass human diagnostic accuracy, challenges related to model training on limited databases persist (Bechelli, 2022).

In conclusion, the literature collectively underscores the transformative potential of machine learning and deep learning techniques in enhancing the accuracy of prostate cancer diagnosis using ultrasound images. Despite the promising advancements, the field faces critical challenges, particularly regarding the need for robust datasets, the integration of AI into clinical practice, and the necessity for standardized evaluation criteria. Addressing these challenges will be pivotal in realizing the full potential of AI technologies in improving diagnostic outcomes and patient management in prostate cancer.

DISCLOSURE STATEMENT

Disclosure Statement : The authors have no conflicts of Interest to declare.

REFERENCES

1. Bhattacharya, I., S. Lim, D., Lin Aung, H., Liu, X., Seetharaman, A., A. Kunder, C., Shao, W., J. C. Soerensen, S., E. Fan, R., Ghanouni, P., J. To'o, K., D. Brooks, J., A. Sonn, G., & Rusu, M., 2021. Bridging the gap between prostate radiology and pathology through machine learning. [PDF]
2. Akatsuka, J., Numata, Y., Morikawa, H., Sekine, T., Kayama, S., Mikami, H., Yanagi, M., Endo, Y., Takeda, H., Toyama, Y., Yamaguchi, R., Kimura, G., Kondo, Y., & Yamamoto, Y., 2022. A data-driven ultrasound approach discriminates pathological high grade prostate cancer. ncbi.nlm.nih.gov
3. Li, H., Hung Lee, C., Chia, D., Lin, Z., Huang, W., & Heng

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved

Tan, C., 2022. Machine Learning in Prostate MRI for Prostate Cancer: Current Status and Future Opportunities. ncbi.nlm.nih.gov

4. Luijten, B., Chennakeshava, N., C. Eldar, Y., Mischi, M., & J. G. van Sloun, R., 2022. Ultrasound Signal Processing: From Models to Deep Learning. [PDF]
5. Hashem, H., Alsakar, Y., Elgarayhi, A., Elmogy, M., & Sallah, M., 2022. An Enhanced Deep Learning Technique for Prostate Cancer Identification Based on MRI Scans. [PDF]
6. Yin, H. & Buduma, N., 2022. Prostate Lesion Detection and Salient Feature Assessment Using Zone-Based Classifiers. [PDF]
7. Bhattacharya, I., S. Khandwala, Y., Vesal, S., Shao, W., Yang, Q., J.C. Soerensen, S., E. Fan, R., Ghanouni, P., A. Kunder, C., D. Brooks, J., Hu, Y., Rusu, M., & A. Sonn, G., 2022. A review of artificial intelligence in prostate cancer detection on imaging. ncbi.nlm.nih.gov
8. Bechelli, S., 2022. Computer-Aided Cancer Diagnosis via Machine Learning and Deep Learning: A comparative review. [PDF]
9. Baek, J., M O'Connell, A., & J Parker, K., 2022. Improving breast cancer diagnosis by incorporating raw ultrasound parameters into machine learning. ncbi.nlm.nih.gov

Downloaded from theInternationalmedicaljournal.org. For personal use only. No other uses without permission.
Copyright © International Medical Journal Corp. Ltd. All rights reserved